

Future Drive Accelerator

Uses the **free memory** as a **cache**, the program reacts automatically on changes in memory resources, so that you will always get the maximum speed for your drives. Even “resources-hungry“ programs will get enough memory.

Version 1.4 (7-May-1999)

by Martin Tauchmann

Copyright © 1998-1999 Martin Tauchmann

This documentation may be copied and spread as long as the copyright note and this copy permission remains unaltered in all copies.

COPYRIGHT

Copyright © 1998-1999 Martin Tauchmann

Future Drive Accelerator is shareware. In this case, that means that you need a personalized version of the program to use the full functionality of **Future Drive Accelerator**.

Users get a personalized version when they have registered with me. This personalized version may not be given to anyone else. To give away the personalized version or to use versions of the program which you did not get directly from me for your personal use, is considered software-piracy.

The personalized version may not be transferred, sold or exchanged to another person or organization. It is solely for the use of the registered person.

You may not use any “patches“ for **Future Drive Accelerator** or publish them (regardless whether they are in text, binary or any other form), except with explicit permission by me for the purpose of updating. Using patched or modified versions of this program is considered software-piracy.

NO WARRANTY

There is absolutely no warranty for this software. Although the author has paid attention on security of data, compatibility and speed while developing this software, he can give no warranty that this program is 100% bug-free. You are using this software solely on your own risk. The author cannot be held responsible for any damages or loss of data that may be caused by this program.

DISTRIBUTION

The demo-version package is “freely distributable“. It may be copied on any media that is used to distribute free software, for example: FD-disks, CD-ROMs, FTP-server and BBS systems.

The full version is not to be distributed.

No program, document or file of this software package may, partially or complete, be distributed with another software package without the written permission of the author.

The demo-version may only be distributed complete and unchanged.

To make sure that the archive is in its original state, distributors should only use the original archives:

Aminet: 'fda.lha' (<http://de.aminet.net/pub/aminet/disk/cache/fda.lha>)
World Wide Web: 'fdaupdate.lha' (<http://home.pages.de/~MartinTauchmann/fdaupdate.lha>)

Programs and documentation may not be modified The only exception is the use of archiving software like LHA, LZX, ZIP or TAR-GZIP/BZIP2, as long as the files can be restored unaltered.

There is no upper limit for distribution costs (cost for disks, tapes or CD-ROMs, or for duplicating them). Such limits have proven harmful for the idea of free software. In some cases, software has been removed instead of lowering the price of a disk below the limit.

Although the author has not set such a limit, he wants to make clear his opinion on the topic:

- This demo software should be available free for everyone, wherever this is possible.
- If you bought this demo software under normal conditions from a PD dealer on a disk and paid more than 5DM/5\$, you have *certainly* paid too much. Please don't support such practices and try to find a better and cheaper source for your software.

RESTRICTIONS OF USE

Future Drive Accelerator may only be used in the way intended by the author, this means it may only be executed on Amiga-computers running AmigaOS. Reassembling, reverse engineering or translation of source code is forbidden.

The documentation and the program texts of **Future Drive Accelerator** are protected by the same copyrights as the program itself. This means the documentation or program texts may not be altered or translated.

To avoid any misunderstandings: You MAY NOT translate the texts or documentation for **Future Drive Accelerator** and distribute them. You must be authorized by me as an official translator. Unauthorized translations of texts and documentation are illegal, harm the copyright and will be removed from public software archives.

No program, document or file from this software package may, partly or completely, be used on machines which are

- used for research, development, construction, test or production of weaponry or any other militarical equipment. This includes machines which are used for training purposes.
- used by persons, who accept, support or use violence against other persons (e.g. foreigners).

Table of Contents

1	The concepts behind Future Drive Accelerator	1
2	What is required to use Future Drive Accelerator?	2
3	What speed improvements can be achieved with Future Drive Accelerator?	3
4	Tested systems	4
5	If you like the demo...	7
	Free Email	9
	Free FAX	9
6	How to install and configure Future Drive Accelerator	9
7	How to configure Future Drive Accelerator..	10
	7.1 The Mainwindow	11
	7.2 The Device Window	12
	7.3 Informations about the drive	15
8	How to quit and monitor Future Drive Accelerator	16
9	Where to send bug reports, comments and orders?	19
10	Compatibility, Features of Future Drive Accelerator	20
	10.1 How to use harddisks bigger than 4 GigaBytes.	21
	10.2 DataSafety	22

11	What will happen to Future Drive Accelerator?.....	23
12	Development history of Future Drive Accelerator.....	23
13	Other products	28
14	The author wants to thank.....	29
Appendix A How to speed up Future Drive Accelerator even more		33
A.1 Better use of ATA[PI] drives		33
A.2 General speedup for turbo boards.....		34
 Appendix B How to use bad memory		34
 Appendix C How to make the Amiga more stable		36
 Appendix D Known bugs		36
D.1 New bug		38
D.1.1 SegTracker, Enforcer und Co.		39
 Appendix E Technical data.....		41
E.1 What programmers should observe.....		43
E.2 Which values are the defaults?		43
E.3 Return values		44
 Index		46

1 The concepts behind Future Drive Accelerator

Future Drive Accelerator is a disk-cache program.

A cache buffers all data which is written or read from the drive (hard disks, floppy disks, Compact-Disk, removable disk, ZIP. . .).

If requested data is already in the cache, it doesn't need to be loaded from the slow disk.

So far nothing new!

Memory is, as we all know, always short. So you better think twice before you give it to programs. No matter how you set it up, you can never make it suitable for all programs. One program runs (thanks to the cache) faster than ever before, another one stops working (due to the lack of RAM).

With all other cache programs, you had to adjust the memory usage. Of course, the more memory a cache can use, the faster it will work. So with old cache programs the memory usage had been set quite high, but because other programs stopped working this was stopped rather quickly. Now the cache is commonly set to an average size, so that all "memory-eating" programs run.

Or you always had to change the cache-size manually to fit the current situation. But this is not a very satisfactory solution. And this is where Future Drive Accelerator comes in.

The whole free memory, whose size is changing all the time, **is used as cache**.

With this technique, an **Amiga** with a 68030 50Mhz processor and 16 MByte FastMemory (Blizzard IV) averages a **factor 4** speed up. See [Chapter 3 \[Benchmarks\]](#), [page 3](#).

Write accesses are buffered, and later, while **writing back** to the drive, the head is moved from the highest to the lowest address.

Another improvement is built-in for people who use exchangeable media like disks, CDs, MagnetOptical-disks and ZIPs. When inserting the media

What speed improvements can be achieved with **Future Drive Accelerator**?²

again, the still filled cache is used. The media doesn't need to be accessed again.

Who used a lot of dos-buffers?¹ for the file system, you can now even save this memory.

Not to mention that you **help protecting the environment**. The motor and the electronics of the drive is used less and thus, energy is saved.
⇒ the **nuclear power plants** can be shutted down earlier.
You should also keep in mind that the **hardware** wears out less.

2 What is required to use Future Drive Accelerator?

Future Drive Accelerator needs at least:

AmigaOS 2.0

or better.

2 Megabyte memory, more memory is recommended.

Additionally, the following software is supported:

DiskSafe

(<http://de.aminet.net/pub/aminet/disk/salv/DiskSafe.lha>)

After a reset or system crash, the cache will be written back before restarting the system.

Example installation for 's:Startup-Sequence':

```
DiskSafe DF1: DF0: HD0: Store: Font: HD2: HD3: HD4: ... REBOOT QUICK-  
KEY WAITVERIFY VERIFYREQ LOGFILE=Store:T/DiskSafe.log IGNORE
```

If this shouldn't work, try adding RESETKEY.

CopyMemQuicker

See [Appendix A \[Speed up\]](#), page 33.

FileSystems, Devices

See [Chapter 10 \[Features\]](#), page 20.

¹ A dos-buffer requires (per default) a half KiloByte.

3 What speed improvements can be achieved with Future Drive Accelerator?

- Copies 850KB in **35 seconds** from hard to floppy disk, this equals the speed of formatting. This is possible because, minimizes the overall seek time required to read or write data from or to disk. Outstanding I/O requests are ordered such that they can all be performed “**with one sweep**“ of the disk head assembly, from the highest to the lowest disk address (Elevator seeking).
- **23 MB/s** while reading, (SysInfo V3.23) instead of 7 MB/s without cache, with an Amiga and following equipment: Zorro III, CyberStorm MKIII, 060/PPC 604 150Mhz, UltraWide SCSI HD, 64 MB FastMemory, CopyMemQuick 40+.
- The booting can get twice as fast if there are a lot of small files to load and many files reside in the ‘WBStartup’ directory.
- Faster access to directories from Workbench.
- Amiga MC68030 50MHz, 16MB FastMemory.
 - IDE-HardDisk (tested with DiskSpeed)²

```

read  6.8 times faster.
write 8.1 times faster.
```
 - DD-FloppyDisk (tested with DiskSpeed)

```

read  488.0 times faster.
write 997.6 times faster.
```
 - Copying from one partition to another.

```

44 Dirs, 561 Files = 2.3MB Size
c:Copy MUI: ASWAP:MUI ALL CLONE QUIET

Dos  457 Dos-Buffers  46 secs 253999 micros
FDA   7 Dos-Buffers  11 secs 196642 micros (4.13 times faster)
```
- Amiga PPC604 233MHz MC68060 50MHz, 96MB FastMemory.
 - IDE-HardDisk (tested with DiskSpeed)

```

read  19.5 times faster.
write 20.4 times faster.
```
 - SCSI-HardDisk (tested with DiskSpeed)

```

read  3.8 times faster.
write 3.5 times faster.
```

More (graphical) statistics, which have been created using DiskSpeed can be found in the guide-file ‘FDA-Benchmarks’.

² DiskSpeed Reference: 262144 byte, MEMF_FAST, LONG-aligned buffer.

4 Tested systems

Hardware List

A4000/40/40Mhz PPC 200Mhz + 64 Fast
CVPPC + 8Mb
Zip Drive
Oktagon Controller
1.3Gb SCSI II Hard Drive (1 partition)
4.3GB SCSI III Hard Drive (3 partitions)
Toshiba 12xCD
IOBlix Super Fast Serial Card
Epson GT-6000 Flatbed Scanner
Pace 56 Voice (V90)(ISP=Wirenet)
Micronik A4000 Tower case
Epson Stylus Color 800
External floppy Drive
Minolta 7000 Camera
External Speakers
MicroVitec GPM 1701 Monitor
Tabby (Drawing Pad)
Sound Sampler
Prelude Sound Card

Software Most Often Used

AHI (music to your ears - registered)
All Experimental PPC Software
PFS2 (So so fast)
CybergraphX V4 (Good with CVPPC)
PPaint 7.1 (It's all in the eye of the beholder)
ImageFX Ver 3.2 (Very stable at this upgrade)
Netconnect (Kiss - Keep It Simple Stupid)
Miami (Works great with my IOBlix)
Turboprint 6.02 (Faster now as it's using the PPC Module)
PageStream 3.3a (I love it)
Organiser (Who am I)
Opus Magellan II (My god, it's full of stars)
CandyFactoryPro (Good PPC Program)
Zip Drivers (Backup my Backups)
HappyDT (Sometimes crashes Netconnect and other programs)
Elastic Dreams (Game for a laugh)

Future Drive Accelerator

Cyberview (Registered)
Cybershow (Registered)
AK-Datatypes (Registered)
Quicksampler (Good PD)
MultiCX (Registered)
OxyPatcher (Make Those Programs Burn)
MUI (3.8) (Workbench 4 perhaps?)
Kingcon (No two shells are the same)

Relaxing Software Used

Genetic Species
Foundation
Alternate Reality (RPG)
Bane of the Cosmic Forge (RPG)
Bards Tale (RPG)
Quake
UFO
Dungeon Master 1 & 2 (RPG)
Ultima VI (RPG)
Birds of Prey
Theme Park
Civilisation
Syndicate
Doom
Stratego (PD)
Myst
Colonization
Frontier Elite II
Deluxe Galaga
Shadow Of The First Moon
VChess
JetPilot
Tiny Troops
Blade (Good Iso RPG)
EaglePlayer (Registered)
MrJQuote

Amiga 1200:
+ 2 880KB Floppys
+ 2 MegaByte 32 Bit Fast-Memory
+ Turbo Jet A1230-BOARD (R) Harms Computertechnik
MC 68030+MMU 14.2 MHz Cache Burst VBR=\$0

Future Drive Accelerator

FPU68881 15.4 MHz
 + WesternDigital Caviar 2850 (850MB)
 - since I have this HD, I had to slow down my MC68030 from 28MHz to
 14.2~MHz. If anybody knows a solution, I would really like to know.
 See [Chapter 9 \[Author\], page 19](#).

CPU	:MC 680030 50MHz
Computer	:Amiga 1200
OS	:V 3.0
Controller	:IDE (Buddha)
Memory	:16MB FastMem 2MB Chip
FileSystem	:FastFileSystem 44.5
Hard Disk	:1x Quantum Fireball 3.68 GB
ZORRO-II-Karten	:1x MultifaceIII, 1x Buddha IDE
other cards	:Blizzard 1230 (CPU-PORT)
others	:Micronik Tower mit Zorro II Datherborad
running programs	:Prometheus V2.6, FKey, MouseBlanker, MultiCX V2.78, NewIcons V40.2, PowerIcons V1.0, SleepingPointers V1.0a, Multifax Spooler V3.1, Killclick2

CS PPC 233MHz, 060 50MHz

A4000 MC68040 25MHz 16FastMem

A3000 CSPPS 604/200 060/50
 PicassoII running cybergraphics (will soon be CVPPC)
 4 different SCSI harddisks of which 3 are SCSI-2 and one UWSCSI
 CSPPC-interface.
 DAT-tapestreamer, CD-ROM, 70MB RAM and many things I can't remember.

Amiga 4000 with 68040/40Mhz, about 80MB Fastram, most of it
 on the turboboard, and 3,5MB Fast on the motherboard.
 2nd.scsi.device / scsi.device / ffs/afs/sfs..

Amiga 1200 040/40 2/32MB 2GB TowerhawkII X2 Multiscan
 CPU : MC 68040 40MHz

Future Drive Accelerator

```

OS           : V 3.1
Controller   : IDE
Memory       : 32MB Fast, 2MB Chip
FileSystem   : FastFileSystem 43.19
Hard disk    : 1 2GB-Platte with 2 Partitionen (50MB and the rest)
CD           : 1 4fach-CD-Rom (RandyCD-Rom)
DirOpus5 Magellan is used as Workbench replacement.

```

5 If you like the demo...

If you like this *demo-version* you might want to use the **full version** which features:

- Faster, because the complete free memory is used as cache.
- Unlimited number of cached drives.
- And of course no time limit.

Ordering the full version is easy, convenient and comfortable - 24h a day worldwide!

Prices

- The **full version** is available for only **19,99 DM (\$12.99) (11,99 EUR)**.
- Minus **5,- DM (-\$3) (-2,60 EUR)** if PowerCache, DynamiCache or HyperCache can be leased.
- Minus **4,- DM (-\$2.5) (-2,10 EUR)** if you are **a student, unemployed or a pensioner** ;-). Please add some proof. See [Chapter 9 \[Author\], page 19](#).
- Plus **4,- DM (\$2.5) (2,10 EUR)** (outside Europe 8,- DM (\$5) (4,20 EUR)) shipping, if you can not receive Email. See [\[Free Email\], page 9](#). For an update, just transfer the money to my bank account.
- Update **0,- DM (\$0) (0 EUR)** if it can be sent via Email. See [\[Free Email\], page 9](#).
- Special prices for 10 or more users. Prepaying of licenses and commercial reselling is also possible. Please contact the author for more details. See [Chapter 9 \[Author\], page 19](#).

Ordering

1. Online in the World Wide Web (<http://shareit1.element-5.de/programs.html?nr=10>) SSL encoded.

Future Drive Accelerator

- Credit cards
 - Visa
 - Eurocard/Mastercard
 - American Express
 - Diners Club
 - Wire-transfer
2. per Phone, FAX or E-Mail
 - ShareIt service.
 - (Program-number 102792)
 - [\[Free FAX\]](#), [page 9](#): +49-221-2407278 (Germany)
 - Phone: +49-221-2407279 (Germany)
 - FAX: +1-724-8508187 (USA)
 - Phone: +1-800-9034152 (USA) free
 - Phone: +1-724-8508186 (USA)
 - E-Mail: MartinTauchmann@bigfoot.com
 3. US check

Send \$15.5 to the address below, include the program-number 102792.

ShareIt! Inc.
PO Box 844
Greensburg, PA 15601-0844
USA
 4. Eurocheque

Please fill in the amount in EUR and send to the [Chapter 9 \[Author\], page 19](#).
 5. Bank transfer

Transfer the money in EUR or DM to:

Badische Beamtenbank eG (Germany)
76119 Karlsruhe
Bank Location Number: 660 908 00
Martin Tauchmann

Future Drive Accelerator

Account Nr.: 2473135

Usage: FDA MC68020 <Your E-mail address>

6. Cash (worldwide)

Put the money in an envelope and send it to the [Chapter 9 \[Author\], page 19](#). (Use an envelope where the money can't be seen against the light.)

Free Email

<http://mail.yahoo.com>

<http://mail.angelfire.com>

<http://www.gmx.de>

<http://www.dejanews.com> (No problems with a "FireWall")

Free FAX

[http://www-usa.tpc.int/sendfax.html?destnumber=49 221 2407278](http://www-usa.tpc.int/sendfax.html?destnumber=49%2021%202407278)

6 How to install and configure Future Drive Accelerator

Please use the included installer script to install Future Drive Accelerator. The AmigaOS Installer V43.3 is required. This version can be found in *Aminet*.

Future Drive Accelerator can be started in different ways:

- Move it to the 'WBStartup' directory, and remove the brackets from the tooltype QUIET. (Workbench-Menu -> *Pictogram* -> *Information*)
- or insert this line:

RUN <>NIL: SYS:System/FDA QUIET in the file 'S:Startup-Sequence' after

- SetPatch
- SaferPatches (<http://de.aminet.net/pub/aminet/util/misc/SaferPatches.lha>) or SetMan
- PoolMem See [Appendix A \[Speed up\], page 33](#).

Future Drive Accelerator

- HDOff (not really necessary, but you can then work with the cache when the harddisk is off.)

Future Drive Accelerator uses the following Workbench Tool Types and Shell parameters:

- FROM (Only from Shell)
Specifies the name of the configuration file.
- QUIET Initialising messages are not printed.
This is useful for an installation in the 'SYS:WbStartup' directory, or the 'S:Startup-Sequence'.

7 How to configure Future Drive Accelerator

Future Drive Accelerator can be configured using the Future Drive Accelerator Preference Editor:


The Preference Editor uses the following Workbench Tool Types and Shell parameters:

- FROM (Only from Shell)
Specifies the name of a configuration file to load.
- EDIT (default option)
The configuration can be changed.
- USE The new configuration will be saved temporary.
- SAVE The new configuration will be saved permanently.
- MAINPROGPATH
Directory of Future Drive Accelerator, e.g. 'Sys:System/'.
The configuration ('FDA.prefs') will be saved to the directory.
If Future Drive Accelerator loaded before 'ENV:' is initialized, which is the case when booting from floppy disk, the config will be found anyway.

Future Drive Accelerator

7.1 The Mainwindow

The MainWindow contains a listing of drives. When you select a window, a new window (see [Section 7.2 \[DeviceWindow\]](#), [page 12](#)) will be opened.



Not used FastMemory

For calibration.

How much of your fast memory shall not be used as cache?

60 kiloBytes is a good value here, because a minimal amount of memory is necessary to send messages. This way, memory can be made available faster.

Not used ChipMemory

For calibration.

How much of your chip memory shall not be used as cache?

100%=No chip memory will be used ⇒ which is the fastest setting.

FastMemory first

Off: The cache uses ChipMemory first, then FastMemory.

On: The cache uses FastMemory first, then maybe ChipMemory.

View color flash if track moved or deleted

Off: No color flash is created.

On: There will be a **green** flash, when a part of the cache is moved in the RAM.
 There will be a **red** flash when a part of the cache is removed from RAM.

Rem.: This option is useful to calibrate **Not used Fast- ChipMemory**.

Protect tracks in memory with checksums

Off: The cache is not protected.

On: The cache will be protected from external programs.

Rem.: This is recommended for Intros, games and badly programmed software which change foreign memory blocks. See [Section D.1.1 \[DebugFiles\], page 39](#).

Or if you have bad memory. See [Appendix B \[Mark Bad Memory\], page 34](#).

Remember: The FileSystem itself calculates checksums. If you get an “Warning!-Requester with a “checksum-**error**“, you may not, in no case, press “Cancel“, but instead reboot your Amiga at once!

This may also happen without **Future Drive Accelerator**, but it is not so likely that a program wrote into the dos-buffers accidentally. Dos-buffers just are a “smaller target“.

The buttons at the bottom of the window are used to set the path where the config-file will be saved. The name of the file is ‘FDA.prefs’.


- | | |
|---------------|---|
| Save | The configuration is saved to the ‘ENVARC:’ directory. The new config will be used automatically by Future Drive Accelerator and will survive a reboot. The preferences editor will quit after saving. |
| Use | The configuration is saved to the ‘ENV:’ directory. The new config will be used automatically by Future Drive Accelerator but will <i>not</i> survive a reboot. The preferences editor will quit after saving. |
| Cancel | To quit the preferences editor. All changes will be lost. |

7.2 The Device Window

The following can be set in the Device Window:

Future Drive Accelerator

When data is written back to the drive, if the data should be verified, how much data should be pre-read and how much of the cache can be used by this drive.



Removeable Disk?

Does this drive contain a removable disk?

e.g.: floppy-, CompactDisc-, ZIP, MagnetOptical or SyQuest-drive.

If Removeable Disk is set to Off, then Future Drive Accelerator does not need to know which FileSystem is used, to recognize a disk after re-inserting.

⇒ The initializing of the cache is faster.

Verify write

The data will be checked if it has been properly written.

⇒ Useful for floppy-disk and old hard-disks.

Write

– Through

Data will be saved at once and moved into the cache at the same time (write-retention).

⇒ When the data is read again, it can be accessed by the cache very fast.

– Sync

Like Through with the difference that the data is written to

the drive³ after the writing of the file was completed⁴ .

⇒ The parallel reading and writing is done more gentle in multitasking.

⇒ The program waits for the end of the write-access (Synchron).

– **Async**

Like **Sync**, but the program doesn't wait for the end of the write-access (ASynchron). What means data is written in an instant.

⇒ Additionally, minimizes the overall seek time required to read or write data from or to disk. Outstanding I/O requests are ordered such that they can all be performed “**with one sweep**“ of the disk head assembly, from the highest to the lowest disk address (Elevator seeking).

The cache is written in the background.

⇒ You can write data to the cache, while the cache is writing to the drive.

See [Section 10.2 \[DataSafety\]](#), page 22.

– **Late as possible**

Like **Async** but the data is written as late as possible. This is recommended for Cache-directories of World-Wide-Web browsers or Internetcomputer, where there is (more or less) always data written.

Data is written when memory is needed or **Future Drive Accelerator** exits, and, if DiskSafe is installed, before a Reset/System-crash. See [Chapter 2 \[Requirements\]](#), page 2.

³ Synchron write-back, or the asynchron delay is started when:

- e.Update-command from FileSystem,
- e.Motor-off-command from FileSystem,
- If a program requests memory, and the cache (the whole RAM) is filled with data that has to be written back.
- Disk removed : “You must replace Volume“
- If DiskSafe is installed : Before a Reset or a Guru.
- or if the cache is full with data to write (at least 7 free tracks)

⁴ The end of the write-access is signalled explicit by the FileSystem to make sure that a device, software- or hardware-cache in the harddisk has written the data completely.

Most harddisks have an internal cache of 64 KB.

- For temporary
Like **Late as possible** but data is NOT written before a Reset/System-crash.
⇒ This is useful for directories whose contents don't need to be the same after the reset, for example: `'env:'` `'t:'`.

Async delay

For how many seconds shall the write-back be delayed with Async?

Size of Track

Number of bytes a track⁵ requires in the cache.

⇒ How many bytes shall be **read ahead**?

Reommended values are for harddisks and CDs about 40KB and for floppy disks (2 tracks = 1 cylinder).

If the harddisk is not fragmented, you could achieve a dramatic speed improvement when you set a high value.

If you use two or more harddisks you should use the **same** value for all unit to avoid the fragmenting of memory. This will be improved in future versions.

Cache usage priority

What priority has this drive compared to other drives for caching?

The buttons in the bottom row of the window can be used to activate or deactivate the cache, and to get informations about the drive

Enable Cache active.

Info Shows [Section 7.3 \[InfoWindow\]](#), [page 15](#) about the drive.

Disable Cache inactive.

7.3 Informations about the drive

This window shows informations about the selected drive.

⁵ If only a **block** (part) of the **track** is read, the hardware copies the whole **track** into a buffer and passes on only the requested **Block**.

Future Drive Accelerator makes use of this behavior: It always reads the whole **track** into the cache. Reading of a **Tracks** is a little bit slower than reading a **block**. slow hardware-head, which would be necessary for reading another **block**.

⇒ And the hardware isn't stressed because the requested **block** is already in the cache.

Size of Block

can be modified using the `HDTToolBox©AmigaInc.` or in the mountfile in the directory `'Devs:DosDrivers'` (`SectorSize * SectorsPerBlock`). But this is not recommend, because most programs depend on a value of `512` here.

No of Tracks

Number of tracks. Is also the capacity of the partition, floppy ... multiplied with **Size of Track**.

First Track Number

Start postions of the partition on the harddisk.

Root Track

Depends on the `FileSystem`. Is used by **Future Drive Accelerator** to recognize a floppy/removable disk only.

Name and Dates Position

The position where the partition-name, the date of creation and the date of the last modification can be found. Is used by **Future Drive Accelerator** to recognize a floppy/removable disk only.

Unit Number

Hardware Unit Number.

Device Name.

Name of the `Software-Device`.

Buffer Memory Type

Either `Chip-` or `Fastmemory`. If `"Need! ChipMemory (slow)"` appears here, you should get more recent `Device-Software`, or try to set `BufMemType=1` in `'Devs:DosDrivers'`, because the drive is slower than it needs to be.

4-GByte 'boundary'

If anything else than `"No problems"` appears here, then this partition is beyond the `"4 GB boundary"`; you should make sure that you use a `FileSystem` and `Software Device` that can handle harddisks bigger than **4 GigaByte**. See [Section 10.1 \[FileSystem installation\]](#), page 21.

New Style Device

Supports the `Device-Software` the new device standard©AmigaInc.?

8 How to quit and monitor Future Drive Accelerator

Future Drive Accelerator

Future Drive Accelerator can be monitored and exited using Future Drive Accelerator View:

The monitor accepts Workbench Tool Types and shell parameters:

KILL-FDA Writes the cache to the drive (if necessary) and quits Future Drive Accelerator.

FLUSH Flushes the cache, except for data that has to be written to disk.

UPDATE Writes the cache to the drive (if necessary).

Future Drive Accelerator View is a by-product, which has helped the author while developing Future Drive Accelerator to find the optimal algorithm⁶ for using the cache. The author didn't plan to release this program, but does it now anyway for the curious ones.

Normally, Future Drive Accelerator View is only required to quit Future Drive Accelerator.

The **right** part of the window shows the current **cache structure** (sorted). Above this is a summary of the list, **how many tracks are in memory** and **how many** of them are waiting to be **written** to the drive. On the **left** side you can control how the list should appear.

Finally, at the top, you can see how much of the free memory is used as currently as cache (**Avail Memory**).

A simpler statistic would be of no use, because the cache is always **used at 100%**.

Sorted by

Location Lists the **memory areas** where the cache-parts reside⁷.
The whole cache is listed.

- **Location** Start position of the track in memory.
- **Type** Memory Type

⁶ The used algorithm is required to figure out which tracks is the last in the queue. This is the oldest track, and if there are several tracks of the same age, the tracks with the smallest access counter is killed.

If you know a more effective algorithm, don't hesitate and let me know.

⁷ The cache is a summary of different tracks.

- **Size** Number of Bytes a tracks uses in the cache.
- **Track** Number of Track. No. 0 is the first.
- **Used** Number of accesses to the track.
- **Old Time** (in seconds) since the last access.
- **Parti** Logical partition- or drive-name.
- **DiskName** Virtual partition-, medium- or disk-name.

Above this is written how many tracks are **in the cache altogether** (all free memory) and how many of that must still be written to the disk.

Track	Lists the cache-parts of a partition, medium or disk. – Track Number of track. No. 0 is the first. – Location Start position of the track in memory. – Type Memory typet. – Used Number of accesses to the track. – Old Time (in seconds) since the last access. – Flags • NowBusy Track is read or written. • MustWrite Track must be written.
-------	--

Above this is written how many tracks **of the medium**⁸ are in the cache and how many of that must be written to drive.

The next lines contain

2. the **Unit** the medium/partition belongs to, the name of the **device** and the start postion (track-number) of the partition on the disk.
3. logical partition- or drive-name and virtual partition-, medium- or disk-name.
4. When the medium was created (formatted) and the date of the last modification. (Only Fast-FileSystem)

⁸ A medium can be a partition, an inserted diskette/ a removable harddisk / CD or a removed diskette. . .

Page Up	One page up. <u>Cursor left, Shift+Cursor up</u> .
Page Down	One page down. <u>Cursor right, Shift+Cursor down</u> .
Top	Top of the list. <u>Key T</u> .
End	End of the list. <u>Key E</u> .
Before Medium	Jump to the previous medium.
Next Medium	Jump to the next medium.

9 Where to send bug reports, comments and orders?

The author can be reached through the following addresses:

Postal addresse:

Martin Tauchmann
Scheffelstr. 49
79102 Freiburg im Breisgau
GERMANY

E-Mail:

MartinTauchmann@bigfoot.com

Sometime you can find me in IRC at "irc.uni-stuttgart.de" in the "#amiga"-channel as NickName "Gaddis".

There is also a Future Drive Accelerator homepage in the World Wide Web, with cyberlinks to "**Super Find Engines**" and many other usefull cyberlinks:

Germany (<http://MartinTauchmann.home.pages.de>)

U.S.A. (<http://bigfoot.com/~martintauchmann/>)

The Pretty Good Privacy (PGP) "PublicKey" is available with Finger, or via WWW (<http://horowitz.surfnet.nl:11371/pks/lookup?op=index&search=0xF74B8D1D>).

ICQ, aka UIN is on my HomePage.

Future Drive Accelerator

10 Compatibility, Features of Future Drive Accelerator

- Accelerates all kind of media e.g.*: Harddisk-, Floppy-, Compact-, ZIP, MagnetOptical- or SyQuest-drives, almost like a RamDrive.
- Uses the **free memory** as **cache** , the program reacts automatically on changes in memory resources, so that you will always get the maximum speed for your drives. Even “resources-hungry“ programs will get enough memory.
- Minimizes the overall seek time required to read or write data from or to disk. Outstanding I/O requests are ordered such that they can all be performed “**with one sweep**“ of the disk head assembly, from the highest to the lowest disk address (Elevator seeking).
- Gentle, parallel reading and writing in Multitasking.
- Smart-Power-Technologie: Minimizes the number of disk-accesses.
- SmartCache: Read-ahead of blocks.
- When disks are removed, the cache is only removed if necessary. When disks are re-inserted, the cache will be used again.
- No fragmentation of memory. (Opposite to DynamiCache.)
- Can possibly save memory, because dos-buffers are not required anymore.
- Power-LED flashes when accessing cache.
- Verify is as fast as in a copy-program, because data is verified in the background while writing. (the processor isn’t used much while writing anyway).
- If DiskSafe is installed, the cache will be written before a reset or system-crash restarts the computer. See [Chapter 2 \[Requirements\]](#), [page 2](#).
- Supports DiskExpander (<http://de.aminet.net/pub/aminet/util/pack/epu14.lha>), Virtual-Memory-Manger (VMM), XFH (<http://de.aminet.net/pub/aminet/util/pack/XFH.lha>) temporal files and World-Wide-Web browsers.
- Supported devices: (probably all
 - scsi (<http://www.amiga.de/files/index.html>), 2nd.scsi, New-StyleDevice, atapi (<http://de.aminet.net/pub/aminet/disk/misc/IDEfix97.lha>), cybscsi,
 - trackdisk, floppy (<http://de.aminet.net/pub/aminet/disk/misc/floppy43.lha>), diskspare (<http://de.aminet.net/pub/aminet/disk/misc/Diskspr3.lha>), hackdisk (<http://de.aminet.net/pub/aminet/disk/misc/NewHackdisk.lha>), mfm.device (©CrossDOS), messydisk (<http://de.aminet.net/pub/aminet/misc/emu/msh-156>),
 - fmsdisk (<http://de.aminet.net/pub/aminet/disk/misc/fmsdisk.lha>),

- xpkdisk (http://de.aminet.net/pub/aminet/util/pack/xpkDisk37_8c.lha),
 - cd.
 - Supported FileSystems: (All knownn)
 - FastFileSystem(FFS), V44.5 (<http://de.aminet.net/pub/aminet/disk/misc/ffstd64.lha>) V43.20 (<ftp://ftp.amiga.com/pub/>)
 - ProfiFileSystem1+2(PFS) (<http://de.aminet.net/pub/aminet/disk/misc/pfs95.lha>), HomePage (<http://www.greed.nl>)
 - AmiFileSafe(AFS) (<http://de.aminet.net/pub/aminet/biz/demo/afsdemo159.lha>),
 - SmartFileSystem(SFS) (<http://www.xs4all.nl/~hjohn/SFS/>),
 - MessyFileSystem(MSD) (<http://de.aminet.net/pub/aminet/misc/emu/msh-156.lha>),
 - CrossDOSFileSystem(MSD) (©CrossDOS),
 - Berkeley (NetBSD LinUX) Fast FileSystem (BFFS UNI\02) (<http://de.aminet.net/pub/aminet/misc/bffs/berkeley.lha>)
- and compatible, furthermore all MultiUser-“clones“.
- Supports FileSystems with a variable block-size.
 - Supports harddisks with a capacity of 4 GigaByte or more.
 - Protects partitions beyond the 4 GigaByte “barrier“ from faulty accesses.
 - Is the fastest cache program. Accelerates harddisks by the **factor 2-20**, floppy disks by the **factor 2-997**.

10.1 How to use harddisks bigger than 4 GigaBytes.

Type *VERSION HDO:* into a shell, to find out if version 44.5 (<http://de.aminet.net/pub/aminet/disk/misc/ffstd64.lha>) or 43.x (<ftp://ftp.amiga.com/pub/>) of the FastFileSystems is installed.

The **new FastFileSystem** version⁹ must be installed into the **Rigid-DiskBlock (RDB)** using HDToolBox. Copying to the L: directoy is not enough.¹⁰

If you have more than one harddisk on your Amiga, **the FastFileSystem is loaded *only* from the Boot-Unit-HardDisk-RDB**. So you have to install the new FastFileSystem into the Boot-Unit; but of course doesn't it do any harm if all Unit-HardDisk-RDB's are updated.

⁹ or SmartFileSystem.SCSIdirect, ProfiFileSystem-2_SCSIdirect.

¹⁰ FastFileSystem V44.5 is not compatibele with `vdisk.device`, `statram.device`, `diskspare.device` and `fms.device`

Reformatting of the partitionen is **not required**, this means the files remain accessible with the new FastFileSystem (<http://de.aminet.net/pub/aminet/disk/misc/ffstd64.lha>). The new FastFileSystem works of course with **IDE-drives**, too.

How do you update the FastFileSystem?

Start the program 'SYS:Utilities/HDTTools/HDTToolsBox':

Select your Boot-HardDisk, 'Partition Drive', 'Advanced Options', 'Add/Update...', **now you can see which version is running in your Amiga**, 'Update File System...', enter *1:FastFileSystem*, 'OK', **now it should read Version: 44 and Revision: 5**, 'OK', 'OK', 'OK', 'Save Changes to Drive', 'Exit'.

10.2 DataSafety

The datasafety of the FastFileSystem is extended with *Write Async* in the case of a power cut.

The ProfiFileSystem-2 and the SmartFileSystem provide datasafety even in the case of a power cut, the medium is always "validated".

The medium is kept "validated" by saving the structure-organizing data to the disk immediatly.

⇒ You could image this as a tree, whose branches have always to be present, the leaves (files) may grow or fall off without harming the tree itself.

New leaves are written to the "list of existing leaves" when the completely grown up. ⇒ Of course, files which were saved during the power cut are lost.

To maintain a valid structure on the medium, the FileSystem must not loose control about the moment of writing, this means the structure must be written "synchron".

⇒ *Write Async* may not be activated, to ensure datasafety during a power cut.

Write Async can be activated, if there is **enough free memory** available to cache the WHOLE write-process.

⇒ The medium is always "validated".

In future versions, using a new FileSystem, datasafety will be maintained during a power cut, even with low memory, using *Write Async*. The impor-

tant structure data (tree) is written “Synchron“ and the files (leaves) “Asyn-cron“.

11 What will happen to Future Drive Accelerator?

The oracle foretells:

- Porting to the new *AmigaOS* QNX.
- New memory-routines. See [Appendix D \[Known Bugs\]](#), page 36.
- Better cooperation with PFS-2 to ensure datasafety during a power-cut. See [Section 10.2 \[DataSafety\]](#), page 22. Furthermore a speedup, because PFS-2 reads and writes directly in the cache.
- Translating the documentation in several languages.
- Porting of oo2c (<http://www.uni-kl.de/00C/>) to the Amiga, which makes it possible, thanks to GNU-C (GCC), to develop Oberon-2 programs for any platform. Oberon-2 is almost identical to Amiga E, ADE 95 (gnat), Modula/Pascal and Cluster.
- Porting of Garbage Collector (http://reality.sgi.com/boehm_mti/) to the Amiga. Replaces C malloc, C++ new as well as C string (cord) which is used for fast string operations.
- New ixemul.library version.

12 Development history of Future Drive Accelerator

1.4, Release date 7-Mai-99

- Brandnew documentation. (Guide, HTML, PS, DVI)
- **Size of Track** is now variable.
⇒ Possible to read more data, before they are needed (read-ahead). ⇒ No fragmentation of memory, if all Units set to the **same Size of Track**.
- Support Virtual-Memory-Manger (VMM). Make in VMM-Prefs Code=No Data=No Program=FDA.
- Fixed, could hang sometimes 1/1.000.000, while writing back Cache.
Because, AbortIO of the Timer Device of OS3.0 has a bug. The Vertical-Blank-Interrupt can jump between the CheckIO and AbortIO of the time-request.

Future Drive Accelerator

⇒ Now doesn't use AbortIO. Restart the Timer if it came back to early.

- Fixed, Checksum-Error, if HD has a capacity more than 2GB (2^{31} "SignedLongWord border").
Because, Oberon has no support for ULongWord (Unsigned).

Replaced all DIV in uDIV, and MUL in uMUL.

IF (highCyl+1) * surfaces > MAX(LONGINT) DIV
ASH(SizeOfTrack,-1) THEN /* HD > 4 GB */

Thanks to Timo Murzo (Master.T.M) Sysop of Unity Mailbox Hamm

Thanks to Michael Kilimann

Thanks to Denis Zwornarz

⇒ Current limit is 1126 GB.

- No further translation of SCSI-direct commands into Track-Disk commands.

If FDA is called with a SCSI-direct command, it uses the same command. ⇒ FFS V44.5 and the special SCSI-direct Versions of PFS-2 and SFS, have no limits (1126 GB) about the HardDisk size. See [Section 10.1 \[FileSystem installation\], page 21](#).

- If the cache (whole memory) is full of data and any other program needs memory, the cache will be written back (flush) and than is memory free again.
- Update-Task (writing back) priority is now one higher than Unit-Task (read/write).

- Fixed, Enforcer hits.

Thanks to Michael Kilimann

- Added ChangeInterrupt. CD-Drives need this, to detect a DiskChanges.

Excluded 'mfm.device' V40.9 (21.05.93), 'multidisk.device' and 'xpkdisk.device' V37.8, because they had a BUG while removeChangeInt.

Device developer: Please, take a look at HackDisk.device Assembler-SourceCode.

Thanks to Marc Michael (yogi)

- Dos-Buffers set to 7.
- Fixed, Dos-Buffers not freed if "QUIET" was used.
- Supported Berkeley (NetBSD LinUX) Fast FileSystem.
⇒protStatus Command detect "Disk Inserted" and Motor off interpreted as "update" Command.
Set the Dos-Buffers of Berkeley (NetBSD LinUX) Fast

FileSystem to 456, because lower values made read errors (found with DiskSpeed V4.2).

- One timer for one Partition, not only one for the whole Unit.
- Fixed, don't turn off the DiskFloppy motor at some systems.

Motor command is again back in the waiting queue.

Developer: Imagine, if you're using SendIO instead of DoIO, the execution is async not only by reading and writing also with the changeState, motor, protStatus, remove, changeNum . . . commands.

Thanks to Herbert Pittermann

Thanks to Jörg Liebelt

- Spared one uDIV Processor instruction. (A modulation and a division in an single uDIV instruction.)
⇒ Little bit faster.
- Little speed up, if an SCSI-direct FileSystem is used.
- Uses exec.GetMsg only if an Message is available (Port.msgList.head^.succ<>NIL).

⇒ Little bit faster (0.44%-0.51%).

- Fixed, printed -1, at verify requester as Track number.
- Fixed, verify retry.
- Fixed, no error number result if an update error exists in Sync-writing-mode.
- Fixed, can't find the icon. QUIET Tooltype now working.
⇒ No window opening, if it's started from WBStartup-Drawer.

Thanks to Harald Wünsche

- Windows are now simple-refresh.
⇒ spares ChipMemory.
- Reduced Stack allocation.
- DSG (Benchmark-Statistics) is now able to read DiskSpeed V4.2 results, but it can't display values greater than 9.9MB.
- Added Blizzard-IV (030 50Mhz) Accelerate-Card benchmarks in the guide.
- Added PPC604 233MHz 060 50MHz Accelerate-Card benchmarks in the guide.
- Preferences:
 - Renamed the Options.
 - Removed "Write-Retention off".

Future Drive Accelerator

- Replaced “ASync-update-writing“ with “Write async = 0 sec“.
- Added “Write as late as possible“, for Cache-directorys of WWW-Browsers.
- Added “Write for temporary“, for t: env: directorys.
- Now, quick toggle device with Shift+LeftMouse.
- Converted “low Track“ to “low Cylinder“.
- Device-List gadget uses the default font, fall back to the topaz.font, if the other text font is proportional or the default font is also proportional.
- Thanks to Andrew Mowatt**
- Thanks to Frédéric Laboureur (Fred) AlphaSOUND - FANTAISIE Software (1998)**
- Added “Size of Block“ of FileSystem in Info.
- Used really New-Look-Menus.
- Fixed, menu “LastSaved“ and “Restore“.
- Fixed, Argumente “USE“ and “SAVE“.
- Reinserted “USE“.
- Fixed, division by zero trap, if no FastMem available.
- Thanks to Flemming Steffensen**
- Fixed, division by zero trap, if “blocks per track“ or “surfaces“ are zero. (NewPortHandler)
- Thanks to Flemming Steffensen**
- Fixed, trap if BlockSize<>0.
- Thanks to Carsten**
- Fixed, no NewStyleDevice detection if anoter unit as zero are used.
- View:
 - View uses the default font; if it’s proportional and the size isn’t 8x8, it falls back to the topaz.font.
 - Thanks to Herbert Pittermann**
 - Thanks to Helge Böhme**
 - Use New-Look-Menus.
 - Thanks to Frédéric Laboureur (Fred) AlphaSOUND - FANTAISIE Software (1998)**
 - Fixed, bad DiskName if another “Size Of Block“ as 512 is used.
- In the Demo Version is writing now possible, but only the half free memory can be used by two drives as cache.
- Price increased by 4.99DM to 19.99DM.

1.2, Release date 20-Aug-98

- Speed up Read/Write little bit.
- Preferences: 'Not used Memory' Proportional-Gadgets are now in Percentage and KiloByte.
Special thanks to Andrew Mowatt
- Better communication between the filesystem and FDA.
Should fix occasional hangings in the previous release.
- Fixed, detect Partitions after 2-GB as 4-GB Partitions.
Support 4-GB HDs is more possible.
Thanks to Timo Murzo (Master.T.M) Sysop of Unity Mailbox Hamm
- Preferences
 - Used New-Look-Menus and scale checkboxes.
Thanks to Frédéric Laboureur (Fred) AlphaSOUND - FANTASIE Software (1998)
 - Unnecessary 'Can't open x.device' removed, if it is not a New Style Device.
Thanks to Marc Michael (yogi)
- Nicer looking MWB icons.
Thanks to Frédéric Laboureur (Fred) AlphaSOUND - FANTASIE Software (1998)

1.0, Release date 20-Jul-98

- Added SmartFileSystem benchmarks in the guide.
- Write operation a little bit faster.
- Fixed, StartUp RangeCheck trap, if `Size of Track > 131072`.
- Dos-Buffers set to 20.
- Supports NewStyleDevice: (NSD) 64-Bit Commands (4GB border).
- Supports scsiCmd (4GB border).
- Preferences
 - Include more "big" HDs.
Thanks to Timo Murzo (Master.T.M) Sysop of Unity Mailbox Hamm
 - DeviceCompatible removed.

0.98, Release date 04-Jul-98

- Supports Partitions after the 4GB border (not tested).
- Speedup Read & Write operations.
- Preferences
 - Includes LateBinding-Devices.

- Preferences: Removed buggy “USE“.

0.96, Release date 25-Mar-98

- First public release @ the AmiNet.

13 Other products

From the same author:

- Future Copper Producer (<http://de.aminet.net/pub/aminet/gfx/edit/FCP.lha>)
 - Convert Pic -> CopperList (6BitPlane -> 0 BitPlane CopperList)
 - CopperListEditor
 - CopperListSearcher
 - Full Modula-2 SourceCode
- Telekom Bill (<http://de.aminet.net/pub/aminet/comm/misc/TelekomBill.lha>)

German Phone-Bill calculator for WG's

- Active Window Picture (<http://de.aminet.net/pub/aminet/gfx/show/ActiveWinPic.lha>)
displays pictures in any window, especial SHELL.
- File 2 Partition (<http://de.aminet.net/pub/aminet/misc/unix/File2Partition.lha>)

Spares memory if LinUX is installed, stores files direct to HD, Disks or any LogicalDevice

- Is Inserted? (<http://de.aminet.net/pub/aminet/util/boot/IsInserted.lha>)
StartUp-Check if a Disk inserted then start BootUte, or any ...
- BrainBird (<http://de.aminet.net/pub/aminet/mods/slow/BrainBird.lha>)

Shaman drums to meditate and 14 Ambient/NewAge/Music concrete Songs.

- Exec.library disassembly (<http://de.aminet.net/pub/aminet/dev/asm/ExecDis.lha>)
A commented disassembly of the exec library 1.2.
- PasTeX ShowDVI-SuperHighRes EpsonMedium/Low (<http://computer.freepage.de/tauchmann/PasTeXShowDVI.lha>) (5.1 MB)
SuperHighRes & Epson medium pk-fonts, other resolutions possible.
⇒ Display 9PinPrinter “Quality“ on Screen.

From other authors (in Aminet):

Future Drive Accelerator

- Better Amiga feeling
 - Copper-rainbows on ALL pubscreens (<http://de.aminet.net/pub/aminet/util/wb/Copper-DerNeedsScreenNotify.library> (<http://de.aminet.net/pub/aminet/util/libs/ScreenNotify10.lha>)
 - PersonalPaint (<http://de.aminet.net/pub/aminet/biz/cloan/PPaint64.lha>) AnimBrush (16 colors) as Mouse-Pointer (<http://de.aminet.net/pub/aminet/gfx/aga/AnimPointer.1ha>) needs AGA/3.0 needs QMouse (<http://de.aminet.net/pub/aminet/util/cdity/qmouse290.lha>) to blank pointer, because MultiCX can't do it.
 - Animated Busy Pointer Hack (<http://de.aminet.net/pub/aminet/util/boot/pointerx.lha>).
 - Time and Mem (<ftp://ftp.uni-stuttgart.de/pub/systems/amiga/amok/amok080/TimeAndMem.lha>) in the Shell-Prompt.
 - AntiTopaz (<http://de.aminet.net/pub/aminet/util/misc/AntiTopaz.lha>) Substitutes topaz with system default font.
- Relax Music
 - DI-* "MagneticNorth" (http://de.aminet.net/pub/aminet/mods/slow/DI-*.lha).

14 The author wants to thank. . .

The development would have been impossible without the feedback of some **Future Drive Accelerator** users. Many ideas and features came from these sources. . .

So I'd like to thank the following persons:

For Alpha-/Beta-Tests, ideas & bug-reports:

Frédéric Laboureur, Michael Kilimann, Denis Zwornarz, Andrew Mowatt, Marc Michael, Herbert Pittermann **Kisses for you sweet Kids**, Harald Wünsche, Timo Murzo, Jörg Liebelt, Flemming Steffensen, Helge Böhme, Andreas, Carsten.

For the translations:

The Amiga Translators Organization (ATO) (<http://ato.vapor.com>)

Jens Neubauer jens.neubauer@gmx.de

For proofreading:

Gregor Knechtges
Heiko Hayn Smeagel@gmx.net

Malcolm Harnden

For supporting the PPC Amiga.

Future Drive Accelerator

Fred Fish Without your **excessive** commitment for the Amiga, I hardly would have gotten those bits and bytes to feed my curiosity. Your new GeekGadget (<ftp://ftp.unina.it/pub/amiga/geekgadgets/amiga/m68k/snapshots>) Project with the GNU ports is **very praiseworthy**. The text you read at the moment has to be partly credited to Fred Fish because it is written in **Texinfo**.

Reinhard Spisser and Sebastiano Vigna
for the Amiga-port of “makeinfo“.

Michael Marte, Hamish Macdonald, Geert Uytterhoeven, Chris Lawrence, Joerg Mayer, Martin Apel, Richard Hirst, Roman Hodek, Thomas Kruse, Benjamin (Benni) Lorenz, Odd-Jarle Kristoffersen, Jes Sorensen, Ron Flory . . . (MC 680xx LinUX)
I can’t find words.

Kamil Iskra, Philippe Brand, Fred Fish, Leonard Norrgard, Hans Verkuil, Gunther Nikl, Anders Wegge Jakobsen (GNU C Compiler)

You made it possible to program for every platform.

Dirk Busse (CopyMemQuicker)

Thanks to your optimising, the cache has become even more faster. See [Appendix A \[Speed up\]](#), page 33.

Matthew Dillon

Without your **DME** (programable text-editor) maybe I had never started typing.

Friedjof Siebert

Without your damn-fast Oberon-compiler, it would have been only half as much fun.

Amiga Modula Oberon Klub Stuttgart AMOK

Your enthusiasm dragged me on. Where do you get all these good ideas from?

Niclaus Wirth

Brought light into the darkness, finally one can read the programs.

Jonathan Potter

Please stay with us. From ScreenX to DOpus, you evolved very much.

Ralph Babel

Very dry, interesting book, in which sect are you now?

Commodore, AmigaInc. . . .

Don’t dare to drop the Amiga like the Hippis the ‘68er. The Amiga is the Harley among the platforms.

Future Drive Accelerator

- Telekom He, I still don't have a modem.
- Quasar (White Box), CodX (Dialer/UnlimitedAcces)
 Really clever how you fooled the Telekom back then.
- William Gibson
 Great books, I still don't understand one word.
- William Gaddis
 Master of the dialogue, pity that your time is over.
- Nico François
 PowerSnap is just great! RequesterTools anyway. PowerPacker
 was a must in times when buying a harddisk costed a fortune.
- Georg Hörmann XFD
 Fixed the old bugs in the decrunchers.
- ASDG FACC
 Your FloppyAccelerator inspired me.
- TURBOBRAIN (D-Copy)
 Your D-Copy (<http://de.aminet.net/pub/aminet/disk/misc/DCopy31.lha>)
 finally brought X-Copy to an end.
- Georg Heßmann
 Your PasTeX made the Amiga able to print.
- ? SoundTracker+
 The author is unknown, so I just thank
 Tracer and DOCTOR MABUSE and UNKNOWN of D.O.C and
 MnemoTroN / Silicon League,
 TIP of THE NEW MASTERS.
- BAMIGA SECTOR ONE, RED SECTOR . . .
 Great intros, just very old.
- Kai Nickel (MathX)
 Another remnant of AMOK. Abitur (school leaving examina-
 tion) is impossible without your program.
- TRIAD (TitanicsCruncher)
 Without your cruncher, one would have to buy RAM all the
 time.
- Bert Jahn WHDLoad (<http://www.fh-zwickau.de/~jah/whdload/>),
 Jean-François Fabre JST
 (<http://perso.club-internet.fr/jffabre/amiga/patches.html>)
 Good work, finally the classic games work with AGA, too, and
 can be loaded quickly from the harddisk.
- BullFrog (Populous, Powermonger. . .)
 It is real fun to play god.

John Matthews (MultiPrint)

What did I have to suffer from print-programs until I found yours! Well, the handling could be easier.

BootX VirusX VirusZ . . .

I believe it was you who killed these poor viruses; and if not you, then it was OS2.0.

Zeitschrift Computing C-16

I find it impossible to print programs on dozens of pages, which you had to type into your computer to play something.

Commodore C-16 PLUS 4

Was fun, especially because you could press some keys and break and disassemble and debug any given program.

Forum InformatikerInnen fuer Frieden und gesellschaftliche Verantwortung
FIFF e.V.

Pretty Good Privacy PGP

Thanks for telling the people about the governmental fooling.

Michael Sinz (MKSoft Development), Bryce Nesbitt

Without DiskSpeed, no one had told me it was getting better.
The Enforcer is absolutly necessary for debugging.

Martin Mares (MJSoft System Software)

Your Resident Module Launcher, and SKick are really good, now you don't have to buy several ROMs each time.

Valenta Ferenc (Copper-Demon)

Great feeling.

Sylvain Rougier (ParM)

Your ParM is my ToolManager.

Stefan Becker (ToolManger)

I used the structure of your documentation.

Richard Körber (PatchWork)

See [Appendix D \[Known Bugs\]](#), page 36.

Thomas Richter (SaferPatches)

DiskSafe (<http://de.aminet.net/pub/aminet/disk/salv/DiskSafe.lha>)
is a nice little tool.

Your SaferPatches (<http://de.aminet.net/pub/aminet/util/misc/SaferPatches.lha>)
solved the problem!

Harry Sintonen (HackDisk)

Your HackDisk assembler-sourcecode answered my questions.

Urban Dominik Müller, Dirk Stöcker, Bryan Ford and Christian von
Roques

Your XPK-system is without competition.

Future Drive Accelerator

all users who decided to register Future Drive Accelerator.

Appendix A How to speed up Future Drive Accelerator even more

So you can make Amiga faster.

Install a CopyMem(Quick)¹¹ Replacement for your processor type:
 68000 (<http://de.aminet.net/pub/aminet/util/boot/COPMQR28.lha>)
 68020 (<http://de.aminet.net/pub/aminet/util/boot/CMQ030.lha>) 68040+
 (<http://de.aminet.net/pub/aminet/util/boot/CMQ060.lha>) The MCP replacement shouldn't be used, because it is slower than these versions.

Set the SCSIsynchron-Flag in the RigidDiskBlock of your boot-harddisk with
 RDBFlags (<http://de.aminet.net/pub/aminet/disk/misc/RDBFlags-1.3.lha>).

Don't use ChipMemory as cache, and set **not used ChipMem** in the preferences, to 100%. See [Section 7.1 \[MainWindow\]](#), page 11.

If you use the program PoolMem, start it with the argument *NoRamReverse*.

A.1 Better use of ATA[PI] drives

You don't have AmigaOS 3.1 and want to install the newest update of the¹² `scsi.device` (<ftp://ftp.amiga.com/pub/>) to get a better performance? (especially together with ATA[PI] drives)

Attention! There is no guarantee for this hack.¹³ The modified file may not be distributed.

The hack works on an 1200 with OS 3.0.

1. Rename the file 'a300.ls.strip', if you use an Amiga 1200¹⁴, to 'scsi.device', and copy it into the 'Devs:' directory.

¹¹ CopyMem(Quick) is used to copy data between cache and system memory.

¹² The hack also works with FastFilesystem V43.20 (<ftp://ftp.amiga.com/pub/>)

¹³ The hack removes an alert which informs the user that no OS3.1 is installed.

¹⁴ If you have another Amiga, please read the 'readme' text in the update-archive, to find out which file is the best for you.

2. Load `'scsi.device'` V43.xx into a file-monitor:
Search for `$0c6c0027`. The next value is `$0014 6516`. Replace `$6516` by `$6026`.
3. Get
AddModule (<http://de.aminet.net/pub/aminet/util/boot/NewAlertH.lha>).

In the first line of your `'s:Startup-Sequence'` write:

```
RUN <>NIL: c:AddModule <>NIL: DEVS:scsi.device CLASS 1 PRI 10
INIT ;V43 CLASS xoper e flags
```

After the second reboot, the new `scsi.device` is loaded.

A.2 General speedup for turbo boards

You have a turbo board, e.g. a Blizzard-IV with Extra Fast Memory?

Is the `exec.library` “function-jump-table” (AVL) in the Chip Memory?
(Can be found out using `X0per` or `FastExec`.)

Get `FastExec` (<http://de.aminet.net/pub/aminet/util/boot/FastExec29.lha>).
Start it with:

```
FastExec SysInfo
```

Is the output for `SysStkUpper` `$xxxxxxxx` a value greater than
`$00200000` if you have 2MB ChipMemory, or
`$00100000` if you have 1MB ChipMemory?

If not, then the “supervisor stack” is in Chip Memory. This slows down the “task-switching”.

Insert this line in your `'s:Startup-Sequence'`, after `AddModule` (if present):

```
FastExec REBOOT FASTSSP FASTMEM
```

Appendix B How to use bad memory

Do your programs crash randomly?

Future Drive Accelerator

Then your RAM-modules may be faulty. Especially PS-2 (SIMM) modules are very vulnerable to “static electricity”.
Or you have some unused RAM-modules laying around?

No need to worry, like on a harddisk, you can mark bad memory and exclude it from usage.

But first we have to know where exactly the memory is faulty. For this purpose there is an excellent program called MemTest (<http://de.aminet.net/pub/aminet/util/misc/MemTest.lha>) which should be started without booting (as much free memory as possible). Beforehand, the “DataCache“ of the CPU should be disabled with

```
CPU NODATACACHE NODATABURST NOEXTERNALCACHE
```

. Now start the “Rotate 32“ test and save the result.

Now get Allocate (<http://de.aminet.net/pub/aminet/dev/misc/allocate.lha>).

Insert at the beginning of your ‘S:Startup-Sequence’:

```
resident c:Allocate pure
Allocate <>NIL: 68900000 100000
Allocate <>NIL: 68B00000 100000
resident Allocate remove
```

The hexadecimal addresses should, of course, contain the bad memory areas. (Be generous, don’t be stingy with a few 100KB or MB (depending on the chip).)

This works with LinUX, too:

Create a ‘file’, where you insert all areas which work 100% okay. For example

```
2097152
0x68000000 9437184
0x68A00000 1048576
0x68C00000 3670016
```

and start AmiBoot with `-m FileName`.

Future Drive Accelerator

Appendix C How to make the Amiga more stable

Do your programs crash with a Guru 4 (Instruction error) or \$1000005 (Memory corrupt)?

The reason could be a too small stack. Every System has a different stack usage, because different programs run in the background, and change system-routines.

If several programs change the same system-routines, this may result in an stack overflow

- which can destroy the free-memory-list,
- or the return address of a subroutine is gone after a task-switch,
- or even other programs are changed accidentally (Enforcer/CyberGuard-Hit).

Even if only one program changes a system-routine and doesn't use stack itself, there are at least 4 Bytes used.

Luckily there is `StackAttack` (<http://de.aminet.net/pub/aminet/util/boot/StackAttack.lha>), Which gives almost every program a little more stack.

example installation in the 's:Startup-Sequence':

```
StackAttack ADDSTACK=512
```

Appendix D Known bugs

If you think you found a bug in **Future Drive Accelerator**, please send a description see [Section D.1 \[New Bug\]](#), page 38 to the author see [Chapter 9 \[Author\]](#), page 19.

Here is a list of known bugs and problems:

Bugs:

- ABackUp has a problem with the RAM-Disk patch of **Future Drive Accelerator V1.4**.
⇒ If a file is packed with XPK and there is no space in the RamDisk,

Future Drive Accelerator

ABackup thinks the file is 2GigaByte large.

Will be fixed in the near future, when the author has completely rewritten the memory-routines.

- **AvailMemory(largest)** gives a value that is too small.
 ⇒ There is a larger continous block; so “not used FastMemory“ can be set to 1%.
 The real value can be determined if you start **Avail** from the shell, then quit FDA, and again start **Avail**.
 Will be fixed in the near future, when the author has completely rewritten the memory-routines.
- If the “**Size of Track**“ is different from disk to disk, the memory will be fragmented.
 Will be fixed in the near future, when the author has completely rewritten the memory-routines.

Not real bugs:

- If Not used **ChipMemory**, see [Section 7.1 \[MainWindow\]](#), page 11 is set to 100%, no track can be moved to make room.
 ⇒ The track is removed from the cache.
 Will be improved soon, when the author has rewritten the memory-routines.
- Doesn't support **AbortIO**, **CloseDevice** yet.
- Supports, but not optimal, **AllocMem(reverse)**.
 ⇒ **AllocMem** reserves a memory area which is the last free. Normally this is in an early region, because the cache is behind. See [Chapter 6 \[Installation\]](#), page 9.
 Will be fixed in the near future, when the author has completely rewritten the memory-routines.
- **ViNCed V3.63** doesn't use **AllocEntry** or **AllocPooled** from **exec** library, to maintain an own poolmemory, to bundle small memory allocations. (It replaces **AllocPooled** with an own routine.)
 ⇒ The cache is very often flushed unnecessary. That's a pity, because for instance the horizontal scrolling is a nice feature.
KingCON V1.3 makes no problems.
 Will be fixed in the near future, when the author has completely rewritten the memory-routines.
- **vdisk.device 2.7 (C) 1994-1997** by Etienne Vogt (like **ramdrive.device**) Doesn't work together, because **vdisk** does not use OS-memory functions. Is not that tragic, because it doesn't support **FastFileSystem V44.5**, too.

Future Drive Accelerator

Future Drive Accelerator has been tested intensively with Enforcer/MungWall and PatchWork.

Patchwork has helped to figure out two very resistant bugs.

- CopyMem(Quick)
size must not only be LongWordAligned (size MOD 8=0), but also Destination & Source. The bug appeared only after several 1000 times and caused chaos in memory.
- CopyMem(Quick)
“memory areas are overlapping (incremental)” seemed to work, but sooner or later, there will be chaos in memory, too, at least with CopyMemQuickerV2.8. This doesn’t mean that CopyMemQuicker is not a good program. See [Appendix A \[Speed up\], page 33](#).

Problems of other cache-programs

- PowerCache
 - Has caused **checksum error** while writing, because Read/Write request are not put in a queue. Especially because the settings are saved to late before a reboot.
 - Cache usage is not flexible.
 - Doesn’t re-use the cache when reinserting a disk.
- DynamiCache
 - Does not support Write Async.
 - Does not support SCSI-direct-FileSystems.
 - Does not support harddisk with more than 4 GigaBytes.
 - Doesn’t re-use the cache when re-inserting a disk.
 - Fragments the memory **extremely**.
 - Does not support AllocAbs and Allocate to free the cache for other programs.
 - If flush is executed (memory full), the cache is deleted, although the memory is not too short anyway.
 - Does not cache accesses from ArtStudioPro 3 and Imagine.

D.1 New bug

1. Which version do you use?

Future Drive Accelerator

2. What was set in FDAPref, see [Section 7.2 \[DeviceWindow\]](#), [page 12](#)? (Removeable Disk?, ...)
3. What says FDAPref, see [Section 7.3 \[InfoWindow\]](#), [page 15](#), about the non-functioning partition?
4. If other programs do not work as they should, do they without FDA?
5. If DOS-checksum (Read/Write) error occurred, please activate FDAPref (Protect tracks in memory with checksummes), see [Section 7.1 \[MainWindow\]](#), [page 11](#). If FDA reports checksum errors, it is not a FDA BUG. Or try to install another FileSystem, if the harddisk has more than 4 GigaByte capacity. See [Section 10.1 \[FileSystem installation\]](#), [page 21](#). Or remove static dust from your RAM-modules. See [Appendix B \[Mark Bad Memory\]](#), [page 34](#).
6. How did the bug appear? How can it be reproduced?
7. Which hardware/software (Mem, OS, FileSystem, Device-Software) was used?
8. Was there a Guru-alert (error messages)?
In FDA are Guru-number (error messages) built-in. These start with \$0FDA00##.

If there was another number, please start SegTracker from the Enforcer-package. Start Tnt or if possible Enforcer or replacement programs like CyberGuard (MC68060). Wait for the bug to show up again.

Write down the error message.

SegTracker is important because the author would like to know when the BUG occurs. See [Section D.1.1 \[DebugFiles\]](#), [page 39](#).

9. If something like this appears, please start Segtracker before.

```
Guru #0005: Division durch 0
Dx 00007FFF 00000000 08C6FFFF 00000000 7FFFFFFF 00000000 081AAE54 00000000
Ax 081AADEC 08C5F9D6 08C5F9DA 08C5F88A 081AAE54 08C5FC34 08000AB0 08C5F820
segment FDAPref
hunk      0
offset 0000365E
sr 0000
pc 08C553E6
<RETURN>
```

D.1.1 SegTracker, Enforcer und Co.

Please read on if you have a processor with MMU, or want to know whether you have.

Future Drive Accelerator

Needed files

Enforcer supports MC68060

(<http://de.aminet.net/pub/aminet/dev/debug/enforcer.lha>),

CyberGuard supports MC68060 DisASM

(http://de.aminet.net/pub/aminet/biz/p5/68060-V44_3.lha),

MungWall to detect Bad written Programs

(http://de.aminet.net/pub/aminet/dev/debug/Mungwall137_64.lzh).

needed to display output (Virtual Terminal) (Work also if the Multitasking is switched off), a replacement for Sushi

(<http://de.aminet.net/pub/aminet/dev/debug/MungFriend.lha>).

How to run Debugging-Tools?

SegTracker (Needed for locate (Hunk-offset) the bug)

RUN Devel:Debug/Enforcer/SegTracker

Enforcer

MultiCX/RebootOff (if MultiCX is running)

RUN Enforcer SHOWPC VERBOSE DEADLY STACKCHECK AREGCHECK DREGCHECK

RAWIO (need MungFriend)

RUN Enforcer SHOWPC VERBOSE DEADLY STACKCHECK AREGCHECK DREGCHECK

FILE=CON:0/0/640/100/Enforcer/Auto/Close

LawBreaker (Any Output? Yes the MMU is working.)

CyberGuard

RUN CyberGuard SHOWPC VERBOSE DEADLY STACKCHECK AREGCHECK DREGCHECK

FILE=CON:0/0/640/100/CyberGuard/Auto/Close PCLINES=4 SHOWDISS

LawBreaker (Any Output? Yes the MMU is working.)

MungWall (Detect bad written Programms (Checksum-Error))

RUN MungWall INFO SHOWFAIL SHOWPC SHOWHUNK SHOWSTACK NAMETAG

Start Output Display Buffer (Virtual Terminal) (MungFriend ON RawSer->CON:)

RUN Devel:Debug/MungFriend INSTALL SIZE 40000 trace flash no-bells noserial

Convert, only, GuruNumber in Hunk-offset, doesn't need an MMU.

Devel:Debug/Tnt FORCE

How to show the output?

Future Drive Accelerator

MungFriend Type to Window

```
Devel:Debug/MungFriend >CON:0/0/696/200/MungFriendSerOutput/Auto/Close/Wait/SHELL
TYPE
```

MungFriend Write to File

```
Devel:Debug/MungFriend Write 'RequestFile DRAWER=SYS:T/ FILE=SerialOutput.txt
TITLE="OutputFile" '
```

MungFriend Clear

```
Devel:Debug/MungFriend CLEAR
```

MungFriend Info (Is any inside?)

```
Devel:Debug/MungFriend INFO
```

MungFriend ON RawSer->CON After Reset/Dead-GURU: (OutPut is still alive)

```
Devel:Debug/MungFriend update trace
```

MungFriend OFF

```
Devel:Debug/MungFriend REMOVE
```

Appendix E Technical data

For curious people, who want to know everything.

- In Exec-Library are patched *AllocMem* (*AllocVec*, *AllocPooled*, *CreatePool*), *Allocate* (*AllocEntry*), *AvailMem*, *AllocAbs* and in the Device~*BeginIO*.
- Memory for the tracks is reserved decreasing (reverse).
- The program was written in Oberon-2 and Assembler.
- One track requires 16 Byte in the cache-structure.
- Using Verify, memory of the size of one track is required per device.
- The TrackDisk64 and SCSI-direct commands support “only” 40-Bit

$2^{40} = 1,0995 \text{ TeraByte} \quad 1125,9 \text{ GigaByte}$

$2^{64} = 18446744,074 \text{ TeraByte} \quad 1,8889465931776e10 \text{ GigaByte}$

The calculation is carried out with a “fast” 32-Bit division.

1226 GByte Harddisks will not be available until the 3rd millenium (by todays standards).

- Only an offset which is divisible by 512 can be used. It would be possible to implement something else, but SCSI-drives don’t support it anyway and there is no known program that doesn’t read/write whole blocks (512 Bytes), so we can save a few bus-cycles here.
- These device commands are understood:

```
‘include:exec/io.h’
```

```
read, write, update,
```

Future Drive Accelerator

```
'include:devices/trackdisk.h'
format, extFormat, extRead, extWrite, rawWrite, extRawWrite,
extUpdate, motor, extMotor, protStatus, getGeometry, getDriveType,
getNumTracks, eject
trackdisk64 (http://de.aminet.net/pub/aminet/dev/misc/trackdisk64.lha)
```

```
read64, write64, format64
NewStyleDevice (NSD)
read64, write64, format64
```

Is used by FastFileSystem V43.x (<ftp://ftp.amiga.com/pub/>).
 ⇒ No problems with harddisks bigger than 4 GigaBytes anymore.
 See [Section 10.1 \[FileSystem installation\]](#), page 21.

Informations about these commands can be found here:
 NSDDocs (<http://www.amiga.de/files/index.html>)
 NSDPatch (http://de.aminet.net/pub/aminet/disk/misc/NSDPatch43_20.lha)

```
'include:devices/scsidisk.h'
scsiCmd
```

SmartFileSystem_SCSIdirect, FastFileSystem V44.5 und ProfiFileSystem-2_SCSIdirect use this command instead of the old trackdisk read/write commands.
 ⇒ No problems with harddisks bigger than 4 GigaBytes anymore.
 See [Section 10.1 \[FileSystem installation\]](#), page 21.

Not all scsiCMD are used, because I don' have a documentation.

```
( SCSIProgrammer (http://de.aminet.net/pub/aminet/dev/misc/SCSIProgrammer.lha) )
( (include:scsi/commands.h SCSI-2 include files) )

( Direct Access devices      =da )
( Write Once devices         =wo )
( CD-ROM devices             =cd )
( Scanner devices            =sc )
( Optical memory devices     =om )
( Sequential access devices  =sa )
( Printer devices            =prt)
( Processor devices          =cpu)
scsiREAD6      =$08 ( da wo cd om )(not tested)
scsiREAD10     =$28 ( da wo cd sc om )
scsiREAD12     =$A8 (   wo cd   om )(not tested)
```

Future Drive Accelerator

```

scsiWRITE6      =$0A (   wo      om )(not tested)
scsiWRITE10     =$2A (   wo      om )
scsiWRITE12     =$AA (   wo      om )(not tested)

```

Has anyone a documentation for these commands?:

```

scsiREAD_BUFFER  =$3C ( da wo cd sc om sa prt cpu )
scsiWRITE_BUFFER =$3B (   wo cd sc om sa prt cpu )
scsiUPDATE_BLOCK =$3D (                om          )

```

E.1 What programmers should observe...

1. Data, which shall be written using the DOS functions `Read/Write`, should be `LongWordAligned` (adr MOD 4=0), because the processor can access them faster then. This also applies to data which is sent directly to a device. `AllocMem`, `Allocate...` automatically return an address that is `LongWordAligned`. So you only have to pay attention if you divide a memory block **manually**.
2. Remember: If you use `SendIO` instead of `DoIO`, the command is executed **Async**. Not only reading and writing, but also `changeState`, `motor`, `protStatus`, `remove`, `changeNum` ... commands.

E.2 Which values are the defaults?

At the first start and after choosing Edit/reset to Defaults from the menu, these values will be used:

```

Create Icons                      = FALSE (OFF)

Not used FastMemory               = 60 KB
Not used ChipMemory               = 50 KB
FastMemFirst                      = TRUE  (ON)
View color flash if track moved or deleted = FALSE (OFF)
Protect tracks in memory with checksummes = FALSE (OFF)

```

```

HD          Async delay           = 4 seconds
Disk        Async delay           = 7 seconds

```

```

Device| Pri | Settings
-----

```

Future Drive Accelerator

```

DF0~ | 100~|~Removeable Disk, Write Async, Verify write
DF1 | 100~|~Removeable Disk, Write Async, Verify write
DF2 | 100~|~Removeable Disk, Write Async, Verify write
DF3 | 100~|~Removeable Disk, Write Async, Verify write
DS0~ | 80~|~Removeable Disk, Write Async, Verify write
DS1 | ~80~|~Removeable Disk, Write Async, Verify write
DS2 | ~80~|~Removeable Disk, Write Async, Verify write
DS3 | ~80~|~Removeable Disk, Write Async, Verify write
PC0 | 60~|~Removeable Disk, Write Async, Verify write
PC1 | ~60~|~Removeable Disk, Write Async, Verify write
PC2 | ~60~|~Removeable Disk, Write Async, Verify write
PC3 | ~60~|~Removeable Disk, Write Async, Verify write
PS0~ | 40~|~Removeable Disk, Write Async, Verify write
PS1 | ~40~|~Removeable Disk, Write Async, Verify write
PS2 | ~40~|~Removeable Disk, Write Async, Verify write
PS3 | ~40~|~Removeable Disk, Write Async, Verify write
CD0 | 20 | Removeable Disk, WriteRetention
HD0 | 0 | Write Async
HD1 | 0 | Write Async
HD2 | 0 | Write Async
HD3 | 0 | Write Async
DH0 | 0 | Write Async
DH1 | 0 | Write Async
DH2 | 0 | Write Async
DH3 | 0 | Write Async

```

E.3 Return values

The return values can be used within a shell-script.

```

Sys:Prefs/FDAPref ENVARC:FDA-AfterBoot.prefs USE
IF WARN ;FDA is not running
    RUN Sys:System/FDA ENVARC:FDA-AfterBoot.prefs QUIET
ENDIF

Sys:System/FDAView >NIL: Kill-FDA
IF NOT WARN ;FDA is running before
    RUN Sys:System/FDA ENVARC:FDA-AfterBoot.prefs QUIET
ENDIF

RUN Sys:System/FDA ENVARC:FDA-AfterBoot.prefs QUIET
IF $RC GE 5 ;FDA is running before
    Sys:Prefs/FDAPref ENVARC:FDA-AfterBoot.prefs USE

```

Future Drive Accelerator

ENDIF

AlreadyRunning	= warn	(5)
PreferenceCancel	= error	(10)
PreferenceFDAnotRunning	= warn	(5)
NoDeviceCached	= fail+1	(20~+1)
CanNotCreatePort	= fail+2	
ReadArgsError	= fail+3	
CanNotReadPrefs~	= fail+4	
CanNotCreateTask~	= fail+5	
AllocSignalError~	= fail+6	
NoMem~	= fail+777-fail	

Index

4

4 GigaByte capacity 15, 20, 21

A

ABackUp 36
AbortIO 36
accelerate 1
active 12
AddModule 33, 34
Addresses 19
AFS 20
Alert 36
Alloc Absolute, mark bad memory 34
AllocAbs (OS) 41
Allocate (OS) 41
AllocEntry (OS) 36
AllocMem (OS) 41
AllocPooled (OS) 36
Ami-FileSafe(AFS) 20
Amiga 1200 4
Amiga 3000 4
Amiga 4000 (040) 4
Amiga E (language) 23
ArtStudioPro 3 36
Assembler 41
Async 43
Async delay 12
Async delay (button) 12
ATA(PI) 4, 20
Author 19
AvailMem (OS) 41
AVL 34

B

Bank transfer 7
Before Medium (button) 17
BeginIO (OS) 41
Benchmarks 3

Berkeley (NetBSD/LinUX) Fast
 FileSystem(BFFS UNIX02) 20
BFFS 20
Blizzard-IV 34
Block 15
Buddha (IDE) 4
Buffer memory type 15
Bugs 36

C

Cache 12, 17
Cache usage priority (button) 12
cache, delete 11
cache, move 11
cache, protect 11
cache-programs, other 36
Cancel (button) 11
capacity 15
Cash 7
change floppy 1
Checksum error 23, 36, 38
checksummes (button) 11
Chipmemory 11, 34
CloseDevice 36
color flash 11
color flash (button) 11
CompactDisk 20
Compatibility 20
concepts 1
Contac addresses 19
Convert 28
Copper 28
copy 3
CopyMem(Quick) (OS) 2, 33, 36
Create 17
Credit cards 7
Credits 29
CrossDOSFileSystem(MSD) 20
CSPPC 4

CVPPC	4
CyberGuard	38, 39

D

DataSafety	12, 20, 22
Default	43
delete cache (button)	11
Device	12
Device Software	15, 17
Devices	2
DirOpus5 Magellan	4
disable (button)	12
Disk name	15, 17
DiskExpander	20
DiskSafe	2, 12, 20
DiskSpeed	3
DoIO (OS)	43
Dos-Buffers	20
Drive informations	12
drives	11
Drives (button)	11
DynamiCache	7, 36

E

Elevator seeking	12
EMail	19
Email, Free	9
enable (button)	12
End (button)	17
Enforcer	36, 38, 39
environment, saved	1
Eurocheque	7
Exec library	28

F

factor	3
FastExec	34

FastFileSystem V43.20	33
FastFileSystem V44.5	21
FastFileSystem(FFS)	20
Fastmemory	11, 34
FAX, Free	7, 9
Features	20
FFS	20
File Monitor	33
FileSystems	2
first (button)	11
First Track number	15, 17
Flags	17
flexible	1
Floppy	20
FLUSH Cache (Argument)	17
Font	23
FROM (Argument)	9, 10
Full version	7
Future	23
Future Copper Producer	28
Future Drive Accelerator	20

G

Guide	3
Guru	36
Guru-Alert	38
Gurunumbers	38

H

Hack	33
hard disk	20
Harddisk, boot	21, 33
Hardware Cache	12
hardware, less used	1
Hardware, UnitNo	15
HDOff	9
HDToolsBox	21
hierarchy	12

History	23
Homepage	19
HTTP	19
HyperCache	7

I

IDE	4, 20
IF (Shell Command)	44
inactive	12
Info (button)	12
Installation	9
Installer V43.3	9
Instruction erros	36

K

KILL FDA (Argument)	17
---------------------------	----

L

L: directory	21
languages	23
leasing	7
LinUX	28
LinUX Berkeley Fast FileSystem(BFFS UNI\02)	20
Location	17
LongWordAlligned	43
low memory	1

M

Mail	19
MainProgPath (Argument)	10
Medium	17
memory	2
Memory corrupt	36
Memory Test	34
Memory type	17

Memory, Bad	34
MessyFileSystem(MSD)	20
MMU	38, 39
Modification	17
monitor	17
Monitor	17
move cache (button)	11
MSDos	20
MultiCX	39
MultifaceIII	4
MungFriend	38
MungFriend After Reset/GURU	39
MungWall	36, 38, 39
Must Write	17

N

nature, saved	1
NetBSD Berkeley Fast FileSystem(BFFS UNI\02)	20
NewAlertH	33
news	1
NewStyleDevice (NSD)	15, 20, 41
Next Medium (button)	17
NoRamReverse	9, 33
not used memory	11
not used memory (button)	11
Now Busy	17
Number of Tracks	15

O

Oberon-2	41
Oberon-2 (language)	23
Old	17
only	7
oo2c	23
Orders	7
OS 2.0	2
overall requirements	2

P

Page down (button)	17
Page up (button)	17
Parti	17
Partition	17
PatchWork	36
PFS	20
Phone	7
PicassoII	4
Picture	28
PoolMem	9, 33
Postal address	19
power cut	22
Power-LED	20
PowerCache	7, 36
PowerPC	4
Preferences	10
ProfiFileSystem(PFS)	20, 22, 23
protect cache (button)	11
PS-2	34

Q

QNX	23
QUIET (Argument)	9
quit	17

R

read-ahead	12, 20
Registration	7
Removeable Disk? (button)	12
Return values	44
RigidDiskBlock	21, 33

S

S:Startup-Sequence	9
SaferPatches	9
Save (Argument)	10

Save (button)	11
SCSI	20
SCSI (UW)	4
SCSI Device	33
SCSI-2	4
SCSI-direct	23, 41
SCSI-synchron-Flag	33
Seconds	43
SegTracker	38, 39
SendIO (OS)	43
set size	1
SetMan	9
SetPatch	9
SFS	20
ShareIt	7
SIMM	34
Size	17
Size of Block	15
Size of Track	17
Size of Track (button)	12
Smart-Power-Technologie	20
SmartCache	20
SmartFileSystem(SFS)	20, 22
Software Cache	12
Sorted by (button)	17
speed	3
Stabl OS	36
Stack, overflow	36
Stack, Supervisor	34
StackAttack	36
start position	15, 17
Static	34
statistics	3
Student	7
supported devices	20
supported FileSystems	20
Sushi	38, 39
SysInfo	3
Systeme	4

T

TeX	28
Thanks	29
time	3
Time	43
Tnt	38, 39
Top (button)	17
Tower with Zorro II Databoard (Micronik)	4
Track	15, 17
TrackDisk64	23, 41

U

Unemployed	7
UNI\02	20
Unit number	15, 17
UPDATE Cache (Argument)	17
update command	12
URL	19
Use (Argument)	10
Use (button)	11
Used	17
uses free memory	1

V

validate	22
----------------	----

vdisk.device (VD0:)	36
Verify	41
Verify write	12
Verify write (button)	12
ViNCed	36
Virtual name	17
Virtual-Memory-Manager (VMM)	36
Virtual-Memory-Manger (VMM)	20

W

WBStartup directory	9
Windows	10, 17
World Wide Web	7, 19
Worldwide	7
Write async (button)	12, 22
Write for temporary (button)	12
Write late as possible (button)	12
Write retention	12
Write sync (button)	12, 22
Write through (button)	12

X

XFH	20
-----------	----

Z

ZIP	20
-----------	----